

CEMTEC CRACK FILLER

CRACK FILLER / FAIR COAT WALL PLASTER



DESCRIPTION

CEMTEC CRACK FILLER is high performance polymer modified crack filler/ fair coat wall plaster. This product can be used for filling cracks up to a width of 8mm in the concrete surfaces.

FEATURES & BENEFITS

- Normal setting times increase workability and reduce waste.
- Fills all cracks and levels the plastered surface and when sanded gives a smooth finish.
- Polymer modified ensures good bonding / flexural strength.
- Can be used in dry as well as wet areas.

BASIC USES

- Filling cracks and holes in concrete
- Levelling uneven surfaces
- For smoothing cracks and holes at door frames.
- Can be used for interior / exterior applications.

SPECIFICATIONS / COMPLIANCES

CEMTEC CRACK FILLER complies with the requirements of ASTM C 473-97 Clause 10 and ASTM C 587-97 Clause-5.

TECHNICAL INFORMATION

Working Life : Approx 1 hour
 Fresh wet density : Approx 1700 kg/m³
 Water addition : 0.48 liter / kg
 Color : White powder

Note : Working life and setting time will vary depending on ambient and substrate temperature.

SHELF LIFE

12 months when stored in shaded dry place in original un-opened bags.

DIRECTIONS FOR USE

Surface Preparation - the concrete must be clean and rough. All oils, dirt, debris, paint and unsound concrete must be removed.

Mixing

Mix 1-1.5 parts of powder into 1 part of clean potable water. Small quantities can be mixed by hand. Care should be taken to ensure that **CEMTEC CRACK FILLER** is thoroughly mixed.

APPLICATION

As a crack filler: Remove all loose particles or wallpaper from holes. The mixed product should be pressed firmly into the cracks by spatula, putty knife or trowel.

As a finish coat: The mixed product should be applied by trowel for leveling the uneven concrete surfaces. Smoothen the surface with sand paper after material is dried.

Curing : **CEMTEC CRACK FILLER** does not require curing with standard methods for most applications. Under hot windy or rapid drying conditions a fog spray or wet cure for 24 hours is recommended after final set of material.

CLEAN UP

Clean tools and equipment with water before the material hardens.

COVERAGE	Contact CMCI Tech Dept
PACKAGING	PACKAGING CEMTEC CRACK FILLER is available in 20 kg bags.
COLOR	Contact CMCI Tech Dept.

Quality Statement

CMCI manufactures its products at their manufacturing facility in Saudi Arabia as per the Quality Procedures certified to conform with quality Management System described in ISO 9000 series

CMCI provides a comprehensive technical support system for its full range of high performance construction products CMCI also offers full technical field support to consultants, Architects, contractors, applicators and End Users.

The Technical Specification information and recommendations given are based on the current technical knowledge and the user or his representative is recommended to check the suitability of the product CMCI reserves the right to amend the technical characteristic of the product as part of ongoing research and development. As the work execution is beyond the direct and continuous control of CMCI no warranty and or responsibility is assumed on the performance of work completion executed with use of our products.

"High Quality Construction Chemicals"
CONSTRUCTION MATERIAL CHEMICAL INDUSTRIES
P.O. Box 7137, Dammam 31462, Saudi Arabia,
Tel: 00966-13-8471450; Fax: 00966-13-8471575
Email: tech@cmci-sa.com, Web: www.cmci-sa.com