

CEMTEC RENDER

PRE MIXED SAND CEMENT RENDER FOR INTERNAL AND EXTERNAL USE

DESCRIPTION:

CEMTEC RENDER is cement based water resistant render /plaster for concrete, block work and also can be used for repairing or patching of concrete surface. The material is blend of cement, graded sand and chemical additive to provide a render with good handling characteristics.

FEATURES & BENEFITS

- Pre blended to overcome site batched variations.
- Long working time
- Normal setting time increase workability and reduce waste.
- Sprayable with spraying machine.
- Can be applied in hand.
- Ceramic tile can be applied directly on CEMTEC RENDER surface.

BASIC USES

- Resurfacing damage d or deteriorated concrete.
- Exterior or interior application.
- General filling up of concrete.

YIELD

Yield is 0.0165m³ per bag when mixed with 4.2 liters of water.

TECHNICAL INFORMATION:

Working life : Approx 2 hours
Fresh wet density : Approx 1730 kg/m³

SHELF LIFE:

12 month when stored at 25⁰C in original unopened bags.

DESCRIPTION FOR USE:

Surface preparation - the concrete must be clean and rough. All oil , dirt, debris, paint and unsound concrete must be removed. The final step in cleaning should be the complete removal of residue with vacuum cleaner or pressure washing.

Mixing – product is normally mixed with a drill of jiffy type mixer. Add the appropriate amount of clean water for batch size and then add the dry product.

Placement – product should be placed in lifts from 3mm to 6mm. multiple lifts may be placed as long as recommended depth is not exceeded.

Finishing - finish the render to the desired texture and / or match to the surrounding concrete. Do not add water to the surface during the finishing operation.

Curing- to prevent from surface cracking cure as per good concrete practice.

CLEAN UP

Clean tools and equipment with water before the material hardens.

PRECAUTIONS /LIMITATIONS

In adverse temperatures, follow ACI recommendations for hot/cold weather concreting practices.

| | |
|------------------|---|
| COVERAGE | CEMTEC RENDER will cover approximately 2.75 m ² when placed at average depth of 6mm. CEMTEC RENDER may be placed in thickness from 3mm to 15 mm. |
| PACKAGING | CEMTEC RENDER is packed in 25 kg bags. |
| COLOR | Contact CMCI Tech Dept. |

Quality Statement

CMCI manufactures its products at their manufacturing facility in Saudi Arabia as per the Quality Procedures certified to conform with quality Management System described in ISO 9000 series

CMCI provides a comprehensive technical support system for its full range of high performance construction products CMCI also offers full technical field support to consultants, Architects, contractors, applicators and End Users.

The Technical Specification information and recommendations given are based on the current technical knowledge and the user or his representative is recommended to check the suitability of the product CMCI reserves the right to amend the technical characteristic of the product as part of ongoing research and development. As the work execution is beyond the direct and continuous control of CMCI no warranty and or responsibility is assumed on the performance of work completion executed with use of our products.

"High Quality Construction Chemicals"
CONSTRUCTION MATERIAL CHEMICAL INDUSTRIES
P.O. Box 7137, Dammam 31462, Saudi Arabia,
Tel: 00966-13-8471450; Fax: 00966-13-8471575
Email: tech@cmci-sa.com, Web: www.cmci-sa.com